

# PROCUREMENT NOTICE

Procurement No. - STC/PSM/2021/PRO - 43
Invitation for Bids for the Purchase of 160,000 Liters of (Coal Tar) Creosote Oil

The Chairman, Procurement Committee, State Timber Corporation, 82, Rajamalwatta Road, Battaramulla now invites sealed bids from Manufacturers, Principals, Suppliers or their accredited Local Agents for the supply of the above items.

- 1. Bidding will be conducted through International Competitive Bidding Procedure.
- 2. Bidders may purchase bidding documents from the Manager (Purchasing & shipping) at the above address.
- 3. To be eligible for a contract award, the successful bidder shall not have been defaulted.
- 4. Interested bidders may obtain further information from the Manager (Purchasing & Shipping) at above address over the Telephone Number 011-2866601-04. Bidding documents may be inspected free of charge at the office of the Manager (Purchasing & Shipping).
- 5. A complete set of Bidding Documents in English language may be purchased by interested bidders on submission of a written request to the Manager (purchasing & Shipping), State Timber Corporation, 82, Rajamalwatta Road, Battaramulla till 22.04.2022 from 09.00 hours to 15.00 hours on normal working days upon payment of a non-re fundable document fee of Rs. 3,500/= in cash per one set of bidding document.
- 6. Bids shall be delivered to the Chairman, Procurement Committee, State Timber Corporation, No.82, Rajamalwatta Road, Battaramulla on or before 10.30 hrs on 25.04.2022 Bids will be opened soon after closing in the presence of the bidders, representatives who choose to attend.
- 7. All Bids shall be accompanied by a bid security equivalent to the value of USD 4500/= of the bid value for a period of 118 days.
- 8. Pre Bid meeting will be held on 07.04.2022, 1030 Hours at "Saptha Parisara mandapaya, No.82, "Sampath Paya" Baththaramulla.

Chairman State Timber Corporation. The state of the s

# SPECIFICATION FOR COAL TAR CREOSOTE FOR PRESERVATION OF TIMBER

# 1 Scope

This specification established requirements for Coal Tar Creosote used for the preservation of timber. (Type II)

# 2 Description

This Creosote shall consist wholly of a blend of distillates of Coal Tar and shall be free from any admixture of Petroleum oils and oil not delivered from Coal Tar.

# 3 Specification

If "NO" comments on the			
Bidder' Respons (YES/NO)			
Minimum Specification	1003 Kg/m3 < 1108 kg/m3	The material shall become completely liquid on being slowly warmed at 38 °C °F) with stirring and on cooling shall remains completely liquid after standing for two hours at 32 °C °F)	If Creosote is required for cold application it shall become completely liquid on being slowly warmed to 38° C°F) with stirring shall on cooling remain completely liquid after standing for two hours at °C. °F)
Component	Density of the material at °C	Liquidity .	
Item # Nam e	1	=	

																			•			
not yield more than 1.5% by	30° C, 315° C, 355°C shall below.		Cumulative Distillate	Not more than % (m/·m)	5	30	82	06	ser, it shall be	ue after separate	F) soft and not sticky.	Id not be a sludge when	re (30°C).	The Distillate to 315° C produced from the material	in 20 ml. of extractable	distillate.	density at lower than 1.06 g/ ml	not less than 5 ml. of extractable phenols per 100 g.		not yield more than 0.4 percent	gh of matter insoluble in	
The material shall not yie volume of water.	The distillates at 205° C, 230° C, 315° C, 355°C shall be within the limits given below.	Distillation Limits		Not less than % (m/ m)		2	C 40	C 73	If required by the purchaser, it shall be	demonstrated to the residue after separate	distillation to 315°C (599°F) soft and not sticky.	The material offered should not be a sludge when	stored at room temperature (30°C).	The Distillate to 315° C pr	shall contain not more than 20 ml. of extractable	phenols per 100 g. of the distillate.	Creosote having a density	not less than 5 ml. of extra	distillate.	The material shall not yie	m) by wei	Tol u ene.
Water Content	Distillation		Temperature		205° C	230°C	315° C	355°C	Residue					Extractable Phenol Content	(Taracids)					Matter insoluble in Toluene		
	2								٨					i						vii		

viii	viii Viscosity	The Kinematic viscosity of the material shall not
Space and a	•	less than less than 4 (mm2/ s) and not more than 20
er in design		(mm 2/ s) at 40°C.
ХĮ	Naphthalene Content	The Naphthalene content of the material shall not
		more than 15 percent (15% m/ m)
•	Method of Evamination Analysis	
r	mentod of Evaluation Arialy as	•
	The methods of examination and analysis of the sample preservation of timber.	analysis of the sample shall be those set down in B.S.S. 144 of 1997 Coal Tar Creosote for the
Name:		
Desig	Designation:	
Signs	Signature:	
Date:		
Rubk	Rubber Stamp:	

\*\*\* Pre- bid meeting will be held on 07/04/ 2022, 10.30 hrs. at "Sapthaparisara mandapaya, No. 82, "Sampath Paya", Rajamalwatta Road, Battaramulla. 5/7

## Schedule II

## SAMPLES

- Scaled samples packed in three individual container, containing not less than one litre
   (01) in volume of "Coal Tar Creosote Oil Type 11" should be submitted to Manager
   (Sleepers & Transmission Poles) State Timber Corporation, No. 82, Rajamalwatte Road,
   Battaramulla prior to the closing date of bid, along with the copies of documents
   regarding this import of samples.
- 2. Acknowledgement for the receipt of samples should be obtained from Manager (Sleepers & Transmission Poles) and the original of which should be enclosed with the original tender document.
- 3. The Manufacturer's/Supplier's name should be printed on each container.
- 4. Failure to comply with any of the above shall result in the tender being considered as incomplete and invalid.
- 5. Samples should not be consigned direct to State Timber Corporation and
  We shall not undertake to clear any such samples from air/sea parcel post Offices or
  by air freight.
- On taking delivery of consignment at our Ware House consignment to be checked by ITI
  in the presence of the following representatives:-

i. I.T.I.

Local Agent or Supplier

iii. S.T.C.

Samples drawn will be sealed by all 03 officials. ITI will test 01 sealed composite sample for quality and conformity with B.S. 144 (1997).

If the samples do not conform to the Standard, the balance 10% on the letter of credit will be retained and the 10% Performance Bond will be seized as liquidated damages arising from the default of the seller and not as a penalty. The seller is deemed to have consented to such forfeiture and have no claim on account of damages of any sort or for reimbursement of money from or against the Buyer.

# 5. Inspections and Tests

The following inspections and tests shall be performed:

- The Technical Evaluation Committee must be satisfied that the provided goods are;
  - > Fully compliance with the technical specifications and all other bidding conditions.

After delivered of consignment at our Warehouse, consignment to be checked by ITI in the presence of the following representatives:-

iv. I.T.I.

v. Local Agent or Supplier

vi. S.T.C.

Sealed composite samples will be checked by ITI for test quality and conformity those set down in B.S.S 144 of 1997 Coal Tar Creosote for the preservation of Timber.